

### Camera Specifications

PHD5N1	
Sensor Type	1/3" CMOS
LEDs	0
Illumination	0.1 LUX
Viewing Angle (Diagonal)	170 degrees
Mirror Image (Selectable)	YES
Parking Lines	YES
Water/Debris-Proof	IP67
Audio	NO
Power Supply	9V-12V DC
Current	70mA
Working Temperature	-25°C ~ +65°C
System	NTSC
TV Lines AHD	720
TV Lines CVBS	480
Resolution (HxV)	CVBS 480P / AHD 720P

### Installation Guide



### Multi-configurable AHD / CVBS Camera Kit

1. Tag Mount Camera
2. Standard Front / Rear Camera
3. Flush mount Camera
4. Lip mount Camera
5. Blind Spot Camera



TECHNICAL SUPPORT:  
Phone: 727-592-5991  
Email: support@aampglobal.com  
Chat: EchoMaster.com

© 2021 AAMP Global

PHD5N1 REV. 051823

### Installation Notes

Camera housings use the same 4 screws for mounting the Standard housing back cover and Lip mount housing back cover.  
The camera has a white dot on top indicating for top viewing angle.  
The Flush mount housing uses a 25mm or 63/64" hole saw.

### Box Contents

- ▶ AHD / CVBS Camera (1)
- ▶ Standard Mount Housing with Hardware (1)
- ▶ Blind-spot Housing with Double-sided Tape (1)
- ▶ Lip Mount Housing with Hardware (1)
- ▶ Flush Mount Housing with Hardware (1)
- ▶ Tag Mount Bracket (1)
- ▶ Camera Extension Cable (1)
- ▶ Camera Power/Video Adapters (1)
- ▶ U-Shaped Camera Angle Adjustment Tool (1)
- ▶ Warranty Card

### Assembling The Cameras

**Standard Camera:**  
Insert the camera into the square housing. Make sure the white mark on the camera is on the top where the arrow is on the square housing. Place the back housing over the camera cable and into the square housing. Secure the back housing with the 4 screws.

**Butterfly Mount:**  
Mount the butterfly bracket to the bottom or top of the camera depending on your application with the supplied bolt and washer.

**Tag Mount (License plate):**  
Insert the camera into the square housing. Make sure the white mark on the camera is on the top. Place the back housing over the camera cable and into the square housing. Secure the back housing with the 4 screws. Mount the tag mount to the assembled camera housing with the supplied bolt and washer.

**Flush Mount Camera:**  
Insert the camera into the large metal housing. Insert the medium metal housing through the camera cable and onto the large metal housing. Tighten the medium metal housing by rotating it clockwise until tight. Slide the metal spring clip through the cable and over the large metal housing making sure the large clips are towards the front of the housing. Slide the small metal housing over the cable. Tighten the small metal housing by rotating it clockwise until tight.

### Assembling The Cameras Cont.

**Flush Mount Adjustable Camera:**  
Remove the large rubber grommet inside the metal housing. Insert the camera into the large metal housing. Insert the grommet over the cable and push it into the back of the metal housing, making sure the tapered part of the grommet is facing the front. Insert the medium metal housing through the camera cable and onto the large metal housing. Tighten the medium metal housing by rotating it clockwise until tight. Slide the metal spring clip through the cable and over the large metal housing making sure the large clips are towards the front of the housing. Slide the small metal housing over the cable. Tighten the small metal housing by rotating it clockwise until tight.

**Lip Mount Camera:**  
Insert the camera into the plastic housing. Make sure the white mark on the camera is on the top. Slide the back cover through the cable and to the back of the housing. Secure the back cover with the supplied 4 screws.

**Blind Spot Camera:**  
Slide the cable through the front of the rubber housing and out the bottom. Push the camera into the rubber housing.

**Wiring Diagram**

制图	单位	MM	产品名称	
审核	比例	FREE	机种型号	
核准	材质		图面编号	
日期	图法		标准公差 ± 范围	彩盒±1 说明书±3 外箱±5
东莞市德才电子科技有限公司 DONGGUAN DECAI ELECTRONICS TECHNOLOGY CO.,LTD			版本号	共1页 第1页
地址: 东莞市虎门镇小捷湾德东工业区 Tel:(86) 0769-8511922 85185193 Fax:(86) 0769-85221223				

BY02E442-0  
客户专用说明书 (PHD5N1)  
285\*197mm 157g铜版纸 双面印刷 4色 过哑膜 对折 ROHS